


Flex 2x60led/mb 19,2W 24V RGBW 7500K
Flexible LED strip 2x60led/m 19,2W 24V RGBW 7500K

Specyfikacja:

Technical specifications:

Zasilanie Voltage	24V DC
Moc/mb Power/m	19,2W
Prąd/LED Current/LED	20mA(2835) 3x20mA(5050)
Dioda LED LED type	SMD 5050 RGB SMD 2835
Ilość LED LED quantity	2x60led/m
Kąt świecenia Beam Angle	120°
Przedział temperaturowy Temperature range	7100K-7500K(2835)
Strumień świetlny Luminous flux	R:270mcd/led G:1000mcd/led B:210mcd/led 520lm/m(2835)
Szerokość(mm) Width(mm)	12mm
Sekcja cięcia Cutting section	100mm
Temperatura pracy Work temperature	- 20° C + 60° C
Żywotność Lifetime	50 000h
Poziom ochrony Protection IP	IP20
Gwarancja Warranty	3 lata/years



Długość fali:
Light wavelength:

R:617-627nm
G:520-530nm
B:465-475nm

Możliwość wyboru przedziału temperatury białej diody led od 2700K do 14000K.
Possibility to choose the temperature range of the white LED from 2700K to 14000K.

